



## CABLE GLAND SHROUDS



### PVC SHROUDS

- ASSIST IN PROVIDING ADDITIONAL PROTECTION TO CABLE GLANDS TO IMPROVE THEIR IP RATING
- ACT AS AN EXTRA GUARD AGAINST CORROSION AND THE WEATHER
- MEET AS5000. :1999 V75 ELECTRIC CABLES WORKING VOLTAGES 0.6/1KV
- FLEXIBLE PVC
- RELATIVE DENSITY: 1.3g/CM<sup>3</sup>
- SHORE A HARDNESS: 73+/- 2 UNITS
- TENSILE STRENGTH: 12MPa
- ELONGATION AT BREAK: 370%
- VOLUME RESISTIVITY: 2 x 10<sup>13</sup> OHM CM
- TEMPERATURE RANGE: 0degC - +75degC

PART NUMBER	CABLE DIAMETER mm	OVERALL LENGTH mm	INSIDE DIAMETER (LARGE END) mm	OUTSIDE DIAMETER (LARGE END)mm
SG1	7	70	25	27
SG2	14	70	29	33
SG3	17	85	39.8	41
SG4	25.5	85	48	50
SG5	30	97	56	58
SG6	32.7	110	71	73
SG7	33.7	125	73	75

*STANDARD COLOUR ORANGE – FOR BLACK ADD B TO SUFFIX OF PART NUMBER*