



DON GRAY ELECTRICAL SUPPLIES
Electrical Wholesalers and Manufacturers Agents
312 PASCOE VALE RD, ESSENDON 3040
ph 9 326 2223 fax 9 326 2191
ABN 43 858 523 981

CABLE TIES



- **MATERIAL – NYLON 66**
- **TEMPERATURE RANGE -40degC to +80degC**
- **FLAMMABILITY – U.L. 94V-2**
- **UV STABILITY – EXCEEDS ASTM-D-4066 (15 YEARS NORMAL UV EXPOSURE)**
- **SMOOTH ROUNDED EDGES (WILL NOT CUT INSULATION OR HANDS)**
- **CLOSELY SPACED LOCKING TEETH PERMIT FINE ADJUSTMENT**
- **NO METAL PARTS (HEAD AND PAWL ARE INTEGRALLY MOULDED)**
- **BENT TIP ALLOWS FOR EASIER PICK UP, INSERTION & PULL UP**

PART NUMBER	DESCRIPTION
CT100B	100 x 2.5mm BLACK
CT100W	100 x 2.5mm WHITE
CT150B	150 x 3.6mm BLACK
CT150W	150 x 3.6mm WHITE
CT200B	200 x 4.8mm BLACK
CT200W	200 x 4.8mm WHITE
CT300B	300 x 4.8mm BLACK
CT300W	300 x 4.8mm WHITE
CT380B	380 x 4.8mm BLACK
CT380W	380 x 4.8mm WHITE
CT380X7.6B	380 x 7.6mm BLACK
CT380X7.6W	380 x 7.6mm WHITE
RLT150W	770 x 7.6mm BLACK
RLT150N	770 x 7.6mm WHITE



DON GRAY ELECTRICAL SUPPLIES
Electrical Wholesalers and Manufacturers Agents
312 PASCOE VALE RD, ESSENDON 3040
ph 9 326 2223 fax 9 326 2191
ABN 43 858 523 981

MINIMUM TENSILE STRENGTH:

- **100 x 2.5mm – 50N (5KG)**
- **150 x 3.6mm – 130N (13KG)**
- **200 x 4.8mm – 220N (22.7KG)**
- **300 x 4.8mm – 220N (22.7KG)**
- **380 x 4.8mm – 220N (22.7KG)**
- **380 x 7.6mm – 550N (55KG)**