

## FLEXICON CONDUIT LTP LIQUIDTITE



FLEXIBLE STEEL CONDUIT WITH SMOOTH OIL RESISTANT & HIGH TEMP PVC COATING

GALVANISED STEEL

HELICALLY WOUND

HIGH MECHANICAL STRENGTH

GOOD FLEXIBILITY

**IP67 WITH STANDARD FITTINGS** 

COVER DOES NOT WRINKLE WHEN BENT

TEMPERATURE RANGE -20degC TO +105degC

STANDARD COLOUR: BLACK, ORANGE, GREY

LLOYD'S REGISTER APPROVAL

**RESISTANT TO OILS AND GREASES** 

UV RESISTANT (BLACK) AND SUITABLE FOR EXTERNAL USE

<u>SIZES</u>:

LTP10B 10mm DIAMETER AVAILABLE IN 50m COILS

LTP12B 12mm DIAMETER AVAILABLE IN 25m & 50m COILS

LTP16B 16mm DIAMETER AVAILABLE IN 10m, 25m & 50m COILS

LTP20B 20mm DIAMETER AVAILABLE IN 10m, 25m & 50m COILS

LTP25B 25mm DIAMETER AVAILABLE IN 10m, 25m & 50m COILS

LTP32B 32mm DIAMETER AVAILABLE IN 10m & 25m COILS



LTP40B 40mm DIAMETER AVAILABLE IN 10m & 25m COILS

LTP50B 50mm DIAMETER AVAILABLE IN 10m & 25m COILS

LTP63B 63mm DIAMETER AVAILABLE IN 10m & 25m COILS